

PREMIERWALL FINEST **LOW VOC**

52"-54" Fabric-Backed Contract Wallcovering



PHYSICAL PROPERTIES

Weight 20.0 oz. PLY / 619G/PLM

Roll Size 52-54" x 30yds

Backing Osnaburg

Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

FIRE SAFETY

- Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel test
- Flame spread: 25 / Smoke developed: 45
- Passes NFPA 286 Corner Burn Test

ENVIRONMENT AND HEALTH

- The product has been assessed according to the assessment criteria of the Singapore Green Building product certification scheme.
- Meets California section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 point for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 point for regional materials



ANTI-MICROBIAL FEATURES

PREMIERWALL FINEST can be perforated, with 30 yard minimum requirement, for enhanced permeability. This product is intended for use in buildings that are properly designed and maintained to avoid moisture infiltration, condensation and/or accumulation at wall cavities and wall surfaces, particularly in warm, humid climates. Goodrich wallcoverings contain anti-microbial additives to resist the growth of mildew and bacteria and pass ASTM G-21. These additives will not prevent mold growth if residual wall moisture is in excess of 4% and/or is allowed to accumulate in or behind the walls.

BATCHING

Since slight variations in shading may occur from time to time, it is important that the roll carrying the same batch number be used in any one area.

ORIGIN

USA