



Specifications

Vu Temperate Willow pattern meets or exceeds all Type II requirements of CCC-W-408D and W-101.

Specifications: Performance:

Weight (Avg.): 20 oz/ly (452gr/m²)
Width: 52/54" (132/137cm)
Backing: Non-woven
Installation: Reverse Hang / Straight Across Match
Repeat: V: 18' H: 53'

Custom colors, weights, widths and microventing are available.

Fire Safety:

- ASTM-E84 (GRC) Class A
 - Passes NFPA 286 Corner Burn
 - NFPA 101 Life Safety Code
 - CAN-ULC S102
-

Environmental and Health:

- Phthalate Free
 - Health Product Declaration (HPD) Available
 - Environmental Product Declaration (EPD) Available
 - Meets State of Washington Building Specification for Indoor Air Quality
 - Meets California Section 01350 Indoor Air Quality Standard
 - Aggressive manufacturing materials recovery and reuse program
 - Highly cleanable water-based inks
 - Free of PBDE's (Brominated Flame Retardants)
-

USGBC LEED Support:

- Support USGBC Leed v4 Criteria
 - Materials and Resources; Building Product Disclosure (includes Recycled Content; Construction Waste Management)
 - Indoor Environmental Quality; Low emitting materials
-

Moisture, Mold and Mildew:

Vinyl wallcovering functions as a vapor barrier. If water or moisture becomes trapped between the wallcovering and wall cavity, an increased risk of mold may occur. Consult a building design professional on the proper use of vinyl wallcovering.

A mildew inhibiting agent has been added to help protect against fungal and other microbiological growth. No additives however, will prevent mold growth if moisture is allowed to accumulate and its sources are not eliminated.

Further protection against mold growth may be achieved with Permavent®, a unique microventing technology that literally "breathes," helping manage the mobile moisture in walls.

Warranty:

Vu is guaranteed to be free of defects in workmanship and material for five years. For additional details on moisture management, Permavent, warranty and other Vu innovations, visit our website at vuwallcovering.com.