



Y47896HS Denim Wash

# vycon

Hide & Silk

54" / Type II / 20 oz.

LOW VOC

## Physical Properties

**Weight:** 20 oz. PLY/620 G/PLM 13.3 oz. PSY/451 G/PSM

**Backing:** Osnaburg | **Width:** 54 in./137 cm

**Match:** Straight, random

Custom colors, weights, and micro venting available. Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

## Fire Safety

- Class "A" fire rated-tested in accordance with ASTM E-84 Tunnel Test
- Passes Class "A" NFPA 101 Life Safety Code
- Passes NFPA 286 Corner Burn Test
- Tested in accordance with CAN/ULC S102.2

## Environment & Health

- Contains 10% recycled content
- Certified to NSF/ANSI 342 Sustainability Assessment; ask distributor for details
- Meets California Section 01350 IAQ test requirements for wallcovering
- Can contribute to LEED EQ 4.1 for low-emitting materials, adhesives, and sealants, if used with low VOC adhesives
- Can contribute to LEED MR 5.1 for regional materials

## Warranty

5 year warranty against manufacturing defects. Additional information is available at: [vyconwallcovering.com](http://vyconwallcovering.com)