

# PREMIERWALL SAPPHIRE

52"-54" Fabric-Backed Contract Wallcovering

## PHYSICAL PROPERTIES

---

**Weight** 20 - 25 oz. PLY / 620 – 774 G/PLM  
**Roll Size** 52-54" x 30yds  
**Backing** Osnaburg / Non Woven  
Meets or exceeds Federal Specification CCC-W-408D for Type II Wallcovering

## FIRE SAFETY

---

- Class "A" fire rated - tested in accordance with ASTM E-84 Tunnel test
- Flame spread: 25 / Smoke developed: 45
- Passes NFPA 286 Corner Burn Test

## CLEANING/MAINTENANCE

---

Metallic finishes can be discoloured with the use of caustic cleaners. Thus, we recommend only the use of a mild soap solution for cleaning these products. If stronger cleaning is required, first evaluate the cleaner in an inconspicuous location.

## ANTI-MICROBIAL FEATURES

---

**PREMIERWALL SAPPHIRE** contain mildew and staph resistant additives in the vinyl and plastisol. This provides the wallcovering with resistance to the growth of mildew and bacteria, including mold, fungi, pink stain and black fungal stain.

## BATCHING

---

Since slight variations in shading may occur from time to time, it is important that the roll carrying the same batch number be used in any one area.

## ORIGIN

---

USA