

TOSCA



SPECIFICATIONS

COLLECTION NAME	: TOSCA SQ
YARN	: 100% Nylon 6
CONSTRUCTION	: Tufted Multi-Level Loop
DYE METHOD	: Solution Dyed
GAUGE	: 1/10"
STITCHES PER INCH	: 12 per inch
PILE HEIGHT	: 4mm+/- 0.5mm
TOTAL HEIGHT	: 6.5mm+/- 0.5mm
PILE WEIGHT	: 20 oz/sy (680gm/sm)
TOTAL WEIGHT	: 124oz/sy (4200gm/sm +/- 200g)
PRIMARY BACKING	: Non-woven
SECONDARY BACKING	: PVC
SIZE	: 50 x 50 cm/tile
PACKING	: 20 pcs (5 sm)/box
ANTI-MICROBIAL	: Ultra-Fresh (available as option)


* As with all dyed products, colours are subject to dye lot variations.

PERFORMANCE SPECIFICATIONS

COLOURFASTNESS	: Grade 5 = No Change (AATCC 16)
FLAMMABILITY:	: Class 1 (ASTM E648)
SMOKE DENSITY	: Passed (ASTM E662)
STATIC PROPENSITY	: ≤ 3.5 kV (AATCC-134)
CRI GREEN LABEL PLUS	: GLP6331
SGBC	: EXCELLENT
WARRANTY	: 10 years



TC02 MOCHA



TC05 DOLPHIN




TC07 DENIM




TC08 CHARCOAL


RECOMMENDED INSTALLATION METHODS :




Monolithic



¼ Turn



Brick



Ashlar

