

*Your cover story*



## **WA202 Ready Mixed Wallcoverings Adhesive** **Product Information Sheet**

### **Description**

WA202 Ready Mixed Wallcovering Adhesive is a PVA based product, which has been specially formulated for use with luxury vinyl (both paper and fabric backed), textiles, Hessians, polystyrene tiles, polystyrene coving and polystyrene veneers.

Recommended for use with all kinds of wallcoverings

### **Application**

Stir well before use and apply undiluted, by brush, roller or finely notched spatula, direct to surface, which is to be papered. Assuming that the surfaces are properly prepared then adhesive usage is as non-woven and woven fabric backed vinyls to all normal surfaces. Woven fabric backed vinyl's to new plasterboard surfaces.

Always use in accordance with the wallcovering manufacturers instructions. Always seal container tightly after use.

### **Surface Preparation**

Surfaces should be sound, dry, clean and free from damp, dust and grease. Porous surfaces such as plaster and floated work should be primed with Primer/Sealer in the ration of 1 part primer to 3 parts water and allowed to dry for +5 hours.

Very porous surfaces such as new plaster, concrete, gypsum board, plaster board, chipboard and block board should be sealed with undiluted primer/Sealer and allowed to dry fro +5 hours. Low or Non-absorbent surfaces should be roughened to form a key.

### **Coverage**

WA202 Ready Mixed Wallcovering Adhesive covers approximately 5 square metres per Kilo

### **Cleaning**

Avoid getting Adhesive on decorative surfaces. Any accidental splashes should be removed immediately with a clean, damp cloth or sponge. Tools and equipment should be cleaned with water immediately after use. Wash hands with soap and water after use.

### **Storage**

Protect from frost. Adhesive should be stored and applied in temperatures above 10°C (50°F), Do not use below this temperature.

## **Healthy and Safety**

Avoid contact with eyes. In case of contact with eyes, rinse immediately with water. Remove splashes from skin with soap and water. This adhesive contains fungicides to protect against mould growth and should be kept away from children and animals.

## **Technical Data**

<b>Physical State:</b>	Thick Paste
<b>Form /Colour:</b>	Opaque white
<b>Odour:</b>	Mild
<b>Solubility in Water:</b>	Miscible
<b>Solubility in organics:</b>	Immiscible

## **Grade**

<b>Specific Gravity:</b>	1.080 ± 0.05
<b>Viscosity @ 20°C (in Poise):</b>	2500+
<b>PH:</b>	5.5 - 6.5

## **Packing Specification**

Product/ Pack Size	Quantity per Carton	Cartons/ Drums per Pallet
5 Kilo Bucket	4	30

## **Customs Tariff Code**

35069900

## **Shipping Classification**

Non-Hazardous for shipping purposes.